

Accessoires

Adapter for POF (polymer optical fiber)

Part Number: 1400000078



Applications: - Adapts the patented **2.50 mm FIBERPOINT®** connection to a **1.5 and 2.2 mm outer diameter polymer optical fiber** connection. Consequently you can check both popular fiber connector types with one fiber fault locator.

Parameter	Specification
Side of the FIBERPOINT®	2.50 mm SM-ferrule
Side of the fiber	1.5 and 2.2 mm
Attenuation	typ. < 1.0 dB
Weight	8.5 g

Included in delivery: - Dust cap on both sides
- Plastic foil bag packaging

Adapter for SMA

Part Number: 1400000088



Applications: - Adapts patented **2.50 mm FIBERPOINT®** connection to **SMA 905** connection. Consequently you can check both popular fiber connector types with just one fiber fault locator.

Parameter	Specification
Side of the FIBERPOINT®	2.50 mm SM-ferrule
Side of the fiber	SMA 905 connector
Attenuation	typ. < 1.0 dB
Weight	3.5 g

Included in delivery: - Dust cap on both sides
- Plastic foil packaging

Compliant with RoHS-requirements (2002/95/EG vom 27.01.2003)

Note: The above product specifications are subject to change without notice.



Messkom Vertriebs GmbH

Awarening 38
D-85419 Mauern

Tel: 0049 (0)8764 / 948 430
Fax: 0049 (0)8764 / 948 433

Email: info@messkom.de
Web: www.messkom.de