

CableScout® TV90

TDR Cable Tester for CATV



GREENLEE®
COMMUNICATIONS
A Textron Company

www.messkom.de



For all your Digital Broadband coax testing needs...

If your job is to find faults on coaxial cable, the Greenlee CableScout® TV90 is built for you. Designed specifically for CATV and other coaxial cable applications, the TV90 applies the newest technology to provide both ease of use and coaxial cable testing performance not found in any other TDR. With the TV90, you'll spend less time operating the TDR and more time repairing faults. Simply select the cable type to be tested and the TV90 does the rest. Pulse width, VP, gain, and vertical position are automatically selected and adjusted as you scan the cable. Finding the fault couldn't be faster, just move the cursor to the fault and use the one-button zoom function to pinpoint its location.

On the performance side, the TV90 employs optimized pulsing and sampling, coupled with advanced filtering and signal-processing techniques. You always have a clean waveform for easiest event identification. **SHORT PULSE WIDTH** - The TV90 uses a 6-ns pulse width for close-in resolution. Faults as near as 3 feet from the pedestal are located with ease. **RUGGED PACKAGE** - Best of all, you get all this performance and ease of use in a small, light, rugged TDR package. Come snow, rain, heat, or humidity, the TV90 keeps working because you have to.

FEATURES:

- Large, High-Resolution, Backlit Display
- Splash, Dust, and Shock-Resistant Packaging
- Easy to Use – Anyone Can Use It
- One Button Expand/Full-View Function
- Dedicated 75 Ω F Connector (misst auch 50 Ohm u. Twisted Pair)
- Intermittent Fault Location
- Context-Sensitive Help (Help Screens Available for All Functions)
- Small, Portable, Lightweight Package (2.2 pounds)
- Accurate (± 2 feet up to 200 feet, 1% beyond)
- 4000-Foot Fault-Location Capability (1,3 Km Fehlerortung)
- Internal Cable Types for Fast, Accurate Testing
- Rechargeable Battery Pack

BENEFITS:

- Find Location of Damage In Drops
- Find Impedance Mismatches
- Locate Bad Passive Devices
- Determine Length of Cable

www.greenlee.com

Characteristics

TEST SIGNAL OUTPUT

1/2 sine.

AMPLITUDE (INTO 75Ω)

6ns pulse: 5 V.

12ns pulse: 6 V.

PULSE WIDTHS

6 and 12 ns.

OUTPUT IMPEDANCE

75Ω.

INPUT PROTECTION

200 V, DC + peak AC to a maximum of 440 Hz, 30 second duration.

DISPLAY RANGES

Eight automatic display ranges.

GAIN

0 to 63 dB.

FILTER

High pass, cutoff frequency 150 kHz, plus averaging.

DISTANCE ACCURACY

0 to 200 feet: ±2 feet. (0-60 m: ± 60 cm)

Beyond 200 feet: 1% + zero offset. (über 60 m: 1% + 0-Offset)

DISPLAY

Resolution: 520 x 200 pixels.

Size: 5.25 inches. (Größe: 13 cm)

Type: High contrast LCD.

Backlight: Operator switchable.

DISTANCE MEASUREMENTS

Meters, feet and nanoseconds.

AUTO SHUTOFF TIME

Operator selectable: 5 to 30 minutes.

Disabled.

ENVIRONMENTAL

Temperature Range:

Operating: 0° C to +45° C.

Non-operating: -20° C to +60° C.

Humidity:

Operating: 95% RH, non-condensing at +30° C to +40° C.

Field Usage:

Shock, splash, and dust resistant.

EMI EMISSIONS

EN55011, Class A.

FCC Part 15, Subpart B, Class A.

SAFETY COMPLIANCE

Evaluated to:

UL3111.

CAN/CSA; C22.2, No. 1010.1.

EN61010-1.

Exempt from LVD (Low Voltage Directive).

POWER

Battery Operation:

Battery Type: Six AA alkaline.

Operating Time: Over 4.5 hours with backlight off.

PHYSICAL




Dimensions	mm	inch
Height	141	5.6
Width	211	8.3
Depth	43	1.8
Weight	kg	lb.
Net	1	2.2

WARRANTY

One year parts and labor.

Ordering Information

 = REPLACEMENT PART  = ACCESSORY

CAT NO.	UPC NO.	DESCRIPTION	QTY.
TV90	12600	TV90 CableScout® TDR	1
THM5BAT	60756 	Rechargeable Battery Pack	1
THM5AC	17299 	AC Adapter 110V	1
TS90-0350	17398 	Soft Carrying Case	1

DISTRIBUTOR INFORMATION:

Messkom Vertriebs GmbH
Awarenring 38
D-85419 Mauern
Tel.: 0049 (0)8764 / 948 430
Fax: 0049 (0)8764 / 948 433
Email: info@messkom.de
URL: www.messkom.de

Lieferumfang: Gerät TV 90 mit Textil-Tragetasche, MiMH-Akkupack, Coax-Anschlusskabel, Adapter von Coax auf 2x Krokoklemmen, Batteriehalter für AA-Batterien zum Austausch gegen den Akkublock.

