



DataCenter Density of passive Real Time TAP's (for stationary use)



F1L single TAP 1 3 3 LC 2 SM, MM



F4L QuadTAP 4 3 12 LC 2 SM, MM



F8L MultiTAP 8 3 24 LC 2 SM, MM



F16 MultiTAP 16 1 16 LC 2 SM, MM



F1M4-SR4 single TAP 1 3 3 MTP 2 MM NEW



F2M4-SR4 DualTAP 2 3 6 MTP 2 MM NEW



F4MY-SR4 QuadTAP 4 3 12 MTP 1 to QSFP Y-cable (4pcs included) MM NEW



F8MY-SR4 MultiTAP 8 3 24 MTP 1 to QSFP Y-cable* (8 pcs included) MM NEW



C1R single TAP 1 3 3 RJ45 2 RJ45 for 10/100/1G



C8 MultiTAP 8 1 8 RJ45 2 RJ45 for 10/100/1G



Connectivity for Monitoring Tools

www.profitap.de
sales@profitap.de

V2.2 © Comcraft 2014
all items are subject of change without notice

common for all models per single TAP function:

- For use by two (2) Channel Hard or Software Analyzer/Appliances
- All Link and Monitor Ports at frontside
- Tested with major analysis & monitoring systems
- Conformity: , Made in EU

• Application:

