

Compact Locator CL43

- Affordable and simple-to-use wire and cable locator
- Supports 512Hz, 10kHz and 33kHz frequencies
- Very handy for locating duct sondes
- For outdoor and indoor use



Trace and identify cables on shelves or inside structures using the close range probe



Use the rod probe to locate even deep underground cables and duct sondes




Locate, trace and pinpoint all kinds of targets with the handy CL43

CL43 Compact Locator is a easy-to-use wire and cable and duct sonde locator. Outdoors CL43 can be used to trace and pinpoint underground cables from several metres depth. Indoors CL43 can be used to locate for example floor heating cables and wires inside walls.

CL43 kit does not include a transmitter but it is compatible with all Vesala 10kHz transmitters and sondes, as well as Vesala's 512Hz sonde for cast iron ducts. Furthermore CL43 supports the 33kHz frequency used with some other manufacturers locators and duct sondes.

CL43 setup - typical accessories and their descriptions



CL43 receiver technical specifications

Receiving frequencies

512Hz, 10kHz and 33kHz (32,768kHz)

Adjustments

2 buttons for power on/off, 7-step gain adjustment and change of receiving frequency

Connectors

Male connector for interchangeable probes

LED indicators

Green LED for power on and low battery indication, 12 red LEDs for received signal strength display (24 levels), for firmware version display, for battery status display and for active operating frequency display

Sound indicators

Internal speaker for tracing signal and for other audible indications

Batteries

3pcs. 1.5V IEC LR03 (AAA) alkaline batteries. Low battery warning at approx. 3.7V

Enclosure material & size

Stainless steel and aluminium, 180 x Ø40 mm, weight approx. 230g (batteries included, no probes)

Protection class

IEC 60529 IP44

Environmental conditions

Usage -40...+60°C (dry or moist conditions), storage -40...+60°C (dry conditions)

We will build a setup according to your preference including probes and duct sondes, all packed in a handy case - contact us & ask more!

Simple user interface

CL43 has a simple user interface with only two buttons, 13 LED lights and a speaker. Probes are easy to disconnect making it easy to carry the receiver and a probe even in a pocket.



Probe technical specifications

Dimensions & weight

SA43: 156 x 23 x 20 mm, approx. 90g

SA05: 156 x 23 x 20 mm, approx. 105g

LA43: 70 x 363 x 34 mm, approx. 70 g

Protection class

IEC 60529 IP44 when attached to the receiver

Environmental conditions

Usage -40...+60°C (dry or moist conditions), storage -40...+60°C (dry conditions)